

# Punch driver sets

## Hand hydraulic punch driver & accessories



The compact, lightweight hand hydraulic punch driver makes it easy to punch holes into stainless V2A steel, mild steel, aluminium or plastics with a max. sheet thickness of 3 mm (V2A: 2 mm), due to its high hydraulic force. The cylinder of the punch driver rotates 360° on 3 axles, so maximum flexibility even in hard-to-reach places is provided.

The punch driver can be used with all icotek punches and also with punches of other manufacturers.

### Scope of delivery:

- 1 hand hydraulic punch driver (weight: 2 kg)
- 1 draw stud  $\varnothing$  9.5 mm (3/8" UNF) to  $\varnothing$  19 mm (3/4" UNF), L: 105 mm
- 1 draw stud  $\varnothing$  19 mm (3/4" UNF), L: 130 mm
- 1 spacer
- 1 tube lubricant
- 1 HSS co-pilot drill (multi step drill)
- 1 robust plastic storage case
- Set PRO 16-31: 1 each knockout punch M16 | M20 | M25 | M32
- Set PRO 16-63: 1 each knockout punch M16 | M20 | M25 | M32 | M40 | M50 | M63

## Specifications

Material	Aluminium
----------	-----------

## Advantages & benefits

- Maximum flexibility due to 360° head rotation
- Compact, lightweight aluminum design (2 kg) for fast and easy operation
- High hydraulic force (60 kN, 600 bar) for easy punching
- Robust plastic storage case
- Punch driver also suitable for punches by other manufacturers

## Product types & sizes

### Punch driver set BASIC



Part No.	<b>80000</b>
EAN	<b>4251269316135</b>
PU	<b>1</b>
Punching force	<b>60 kN</b>
Operating pressure	<b>600 bar</b>

### Punch driver set PRO 16-32



Part No.	<b>80005</b>
EAN	<b>4251269316142</b>
PU	<b>1</b>
Punching force	<b>60 kN</b>
Operating pressure	<b>600 bar</b>

**Punch driver set PRO  
16-63**



Part No.	<b>80006</b>
EAN	<b>4251269316159</b>
PU	<b>1</b>
Punching force	<b>60 kN</b>
Operating pressure	<b>600 bar</b>

---

□